BY APPOINTMENT TO HIS MAJESTY KING CHARLES III
PURVEYORS OF FABRICS, PAINTS & WALLPAPERS
SANDERSON, CHISWICK, LONDON

SANDERSON

WATER BASED EGGSHELL

DESCRIPTION
Water Based Eggshell is a premium quality, water-based, low sheen finish formulated for interior use on walls, ceilings, wood and metal surfaces It provides a low odour, quick drying finish that is resistant to condensation and yellowing, making it ideal for use in kitchens, bathrooms, hallways and conservatories.

KEY PROPERTIES
- A quick drying, low odour, low sheen finish for interior use.
- Produces a smooth, washable surface that resists condensation.
- Tough, durable and non-yellowing.
- High opacity and hardwearing.

PREPARATION
All surfaces to be painted should be clean, dry and free from loose and flaking material including dirt and grease. Prime base surfaces with an appropriate primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust and wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces as they may contain harmful lead.

APPLICATION
Stir well before use. Ensure good ventilation during application and drying. Apply by brush, roller or sprayer. Do not overfill paint trays. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading. Apply two coats. Additional coats may be required on new plaster or where a greater colour change is desired. Do not apply in temperatures below 10°C or in damp conditions. If more than one can of colour is to be used in the same area, intermix before use.

CLEANING
Remove as much product as possible from equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

PRECAUTIONS
- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

RECOMMENDED USES
Suitable for interior use.

TYPE OF SUBSTRATE
Wood, metal and plaster. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

COLOUR RANGE
154 colours.

FINISH
Low sheen - 10-25%.

VOLUME SOLID
34%.

COVERAGE
Approximately 12 square metres per litre depending on the nature and porosity of the surface

DRYING TIME
Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

TRANSPORTATION & STORAGE
To avoid the risk of spillage, always store and transport in a secure upright position Protect from frost, store away from heat and flame.

CLEANER
Clean water

VOC CONTENT
- Low VOC (Volatile Organic Compounds) 0.3-7.99%
- EU limit value for this product Cat A/(d): 130 g/L (2010).
- This product contains max 12g/l VOC.

FILM THICKNESS
Wet: 86µm, Dry: 29µm.

SIZES
1 Litre, 2.5 Litre.